


w163 Lampyre t1



Technical information

Physical	
Material	Opal glass
IP rating	20
Protection class	II

LED

Light source

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wästberg Lighting AB apply.

Article-specific information

Version	t1
Mounting	Base
LED Colour temperature (CCT) / Luminous flux	2700 K / 110 lm
Voltage / System power	220–240 V / Max. 24 W LED
Light control	Dimmer switch on cord
Net weight	1.6 kg
Packaging dimensions	L44 × W38 × H16 cm (0.03 m ³)
Gross weight	2.5 kg


Colour

White (similar to RAL 9010)

Art. No. / EAN code

163T100 / 7330492007564

w163 Lampyre t2



Article-specific information

Version	t2
Mounting	Base
LED Colour temperature (CCT) / Luminous flux	2700 K / 110 lm
Voltage / System power	220–240 V / Max. 24 W LED
Light control	Dimmer switch on cord
Net weight	4.2 kg
Packaging dimensions	L63 × W58 × H24 cm (0.09 m ³)
Gross weight	4.5 kg
Colour	Art. No. / EAN code
White (similar to RAL 9010) <input checked="" type="radio"/>	163T200 / 7330492007571